


CODE 3152 - PN 10 / CODE 3142 - PN 16



Gomito a 45° testa/testa - Butt fusion elbow 45° - Coude à 45° bout à bout - Codo a 45° soldadura a tope - Stumpfstoß Winkel 45°
Колено 45° для стыковой сварки



3142

PE100 - SDR11 - S5
ACQUA: PFA (PN)=16 bar 20°C
GAS: MOP=10 bar; in Italia MOP=5 bar (D.M. 24/11/84, D.M 16/4/2008 e successive modifiche)

PE100 - SDR11 - S5
WATER: PFA (PN)=16 bar 20°C
GAS: MOP=10 bar; in Italy MOP=5 bar (D.M. 24/11/84, D.M 16/4/2008 and further modification)

3152

PE100 - SDR17 - S8
ACQUA: PFA (PN)=10 bar 20°C
GAS: MOP=6,2 bar; in Italia MOP=3,7 bar (D.M. 24/11/84, D.M 16/4/2008 e successive modifiche)

PE100 - SDR17 - S8
WATER: PFA (PN)=10 bar 20°C
GAS: MOP=6,2 bar; in Italy MOP=3,7 bar (D.M. 24/11/84, D.M 16/4/2008 and further modification)

DIM dxd [mm]	PN 10 - SDR 17 - S8		PN 16 - SDR 11 - S5		L1 [mm]	L2 [mm]	h [mm]	PACK			
	CODE	e	CODE	e				RIF. 13	RIF. 14	RIF. 15	Sfusi Loose
32x32	-	-	3142032000001	3,0	52	62	120	85	-	-	-
40x40	-	-	3142040000001	3,7	60	70	135	45	-	-	-
50x50	-	-	3142050000001	4,6	60	80	145	30	-	-	-
63x63	-	-	3142063000001	5,8	68	90	165	16	-	-	-
75x75	-	-	3142075000001	6,8	72	95	186	10	-	-	-
90x90	3152090000001	5,4	3142090000001	8,2	82	115	210	-	25	-	-
110x110	3152110000001	6,6	3142110000001	10,0	90	125	225	-	16	-	-
125x125	3152125000001	7,4	3142125000001	11,4	90	130	235	-	11	-	-
140x140	3152140000001	8,3	3142140000001	12,7	90	120	267	-	8	-	-
160x160	3152160000001	9,5	3142160000001	14,6	100	125	290	-	6	-	-
180x180	3152180000001	10,7	3142180000001	16,4	125	183	375	-	-	5	-
200x200	3152200000001	11,9	3142200000001	18,2	132	195	400	-	-	3	-
225x225	3152225000001	13,4	3142225000001	20,5	138	200	452	-	-	-	1
250x250	3152250000001	14,8	3142250000001	22,7	145	200	490	-	-	-	1
280x280	3152280000001	16,6	3142280000001	25,4	160	220	505	-	-	-	1
315x315	3152315000001	18,7	3142315000001	28,6	210	300	600	-	-	-	1